

# ASCOLI FLOOR 4585

SKU 1286025

astro



## PRODUCT SPECIFICATION

### GENERAL

<b>FINISH:</b>	Bronze Effect	<b>CABLE LENGTH:</b>	3000 (mm)
<b>MAIN MATERIAL:</b>	Metal - Mild Steel	<b>GROSS WEIGHT:</b>	6.68 (Kg)
<b>DIMENSIONS:</b>	H: 1225mm W: 200mm D: 285mm DIA: 200mm	<b>CLASS:</b>	CE (Class II)
<b>INSTALLATION ORIENTATION:</b>	Not Applicable	<b>IP RATING:</b>	IP20
<b>CUT OUT HOLE:</b>	Not Applicable	<b>BATHROOM ZONE:</b>	Zone 3
<b>RECESS DEPTH:</b>	Not Applicable	<b>VOLTAGE:</b>	Mains 230 (V)
<b>FIRE RATING:</b>	Not Applicable	<b>PRODUCT F MARK:</b>	Not Applicable

### LAMP


<b>LIGHT SOURCE:</b>	LED GU10	<b>MACADAM ELIPSE:</b>	Not Applicable
<b>MAXIMUM WATTAGE:</b>	6W	<b>UGR:</b>	Not Applicable
<b>MAXIMUM LAMP LENGTH:</b>	To Be Advised	<b>BEAM ANGLE:</b>	Not Applicable
<b>LAMP INCLUDED?</b>	No	<b>TILT ADJUSTMENT ANGLE:</b>	90 (Degrees)
<b>LUMINOUS FLUX:</b>	Lamp Dependent	<b>ROTATION ADJUSTMENT ANGLE:</b>	330 (Degrees)
<b>COLOUR TEMP:</b>	Lamp Dependent	<b>AVERAGE LIFESPAN:</b>	Lamp Dependent
<b>CRI:</b>	Lamp Dependent	<b>L70:</b>	Not Applicable
<b>R9:</b>	Lamp Dependent		

### ELECTRICAL

<b>SWITCHED:</b>	Yes	<b>SUPPLY FREQUENCY:</b>	Not Applicable
<b>DIMMABLE:</b>	No	<b>DRIVER / BALLAST VOLTAGE:</b>	Not Applicable
<b>DIMMING METHOD:</b>	Not Applicable	<b>DRIVER AVERAGE LIFESPAN:</b>	Not Applicable
<b>DRIVER OUTPUT CURRENT:</b>	Not Applicable	<b>EFFICACY:</b>	Not Applicable
<b>DRIVER OUTPUT VOLTAGE:</b>	Not Applicable	<b>DRIVER / BALLAST INCLUDED?</b>	No

## ADDITIONAL INFORMATION

CE



BOX QUANTITY x1

PRODUCT ELEVATIONS

---

