

Oxy new

Extruded aluminum profile compatible with lighting elements with magnetic fixing. The system is powder coated and available in black or white for ceiling installation. The modules can be assembled according to the desired layout and they feature an integrated 1-10V dimming control. The profile section is 26 mm wide and 27 mm or 52 mm high; available in two lengths, 2000 mm and 3000 mm. Possibility of assembly with different source modules: the WIDE diffusing module; the ACCENT module with control of the UGR lower than 13; the TRACK SINGLE or DOUBLE module for spot illumination with different angles of emission and the PENDANT TUBE decorative module. Integrated LEDs, color temperature of 3000 K; starting Binning ≤ 2 -Step MacAdam; IP20 protection, insulation class III. The 48 Vdc power supply gives great versatility and safety, the compositions are in fact reversible and modifiable if necessary. Suitable for the installation in large environments where great flexibility and color rendering is required, such as MUSEUMS, COMMERCIAL, RESIDENTIAL and RETAIL spaces.

Source	LED COB / SMD
Driver included	No
Control	1-10V
MacAdam	SDCM 2
CCT	3000 K
CRI	≥ 90
UGR	<16 (Accent, Pendant)
LED life	35.000 h
Insulation class	III
IP	20
Material	Aluminum
Warranty	5 years

