

Kanlux

ALDO 4LED

OPRAWA LINIOWA POD TUBY LED T8 ▶ T8 LED TUBE LINEAR FITTINGS



ALDO 4LED 1X60; 1X120; 1X150



ALDO 4LED 1X60R; 1X120R; 1X150R



ALDO 4LED 2X60; 2X120; 2X150



ALDO 4LED 2X60R; 2X120R; 2X150R



Model	Code	Part No.	Length	Tube	Base	Color
ALDO 4LED 1X60	26360	5905339263605	max 18	T8 LED	G13	biały white
ALDO 4LED 1X120	26361	5905339263612	max 36	T8 LED	G13	biały white
ALDO 4LED 1X150	26362	5905339263629	max 58	T8 LED	G13	biały white
ALDO 4LED 2X60	26363	5905339263636	2 x max 18	T8 LED	G13	biały white
ALDO 4LED 2X120	26364	5905339263643	2 x max 36	T8 LED	G13	biały white
ALDO 4LED 2X150	26365	5905339263650	2 x max 58	T8 LED	G13	biały white
ALDO 4LED 1X60R	26370	5905339263704	max 18	T8 LED	G13	biały white
ALDO 4LED 1X120R	26371	5905339263711	max 36	T8 LED	G13	biały white
ALDO 4LED 1X150R	26372	5905339263728	max 58	T8 LED	G13	biały white
ALDO 4LED 2X60R	26373	5905339263735	2 x max 18	T8 LED	G13	biały white
ALDO 4LED 2X120R	26374	5905339263742	2 x max 36	T8 LED	G13	biały white
ALDO 4LED 2X150R	26375	5905339263759	2 x max 58	T8 LED	G13	biały white



Kanlux ALDO 4LED to rodzina belek oświetleniowych przystosowanych do świetlówek ledowych T8. Są to oprawy ścienna-sufitowe charakteryzujące się nowoczesnym, opływowym kształtem, przez co dyskretnie wpasują się w każdą aranżację wnętrza.

Oprawy są przeznaczone do źródeł T8 LED 220-240 V-; 50/60 Hz z zasilaniem jednostronnym

ALDO R wyposażona w odbłyśnik

Materiał obudowy: metal, tworzywo sztuczne

Kanlux ALDO 4LED are a family of batten luminaires adapted to T8 LED fluorescent lamps. They are wall and ceiling luminaires characterised by modern, streamlined shape so they fit discreetly in each interior arrangement. Kanlux ALDO 4LED are a family of batten luminaires adapted to T8 LED fluorescent lamps. They are wall and ceiling luminaires characterised by modern, streamlined shape so they fit discreetly in each interior arrangement.

The fittings are intended for sources T8 LED 220-240 V-; 50/60 Hz with one-sided power supply

ALDO R equipped with a reflector

Enclosure material: Metal, plastic

[V] 220-240 AC	[Hz] 50/60	T8 LED		IP 20		 5+25		 0,5-2,5	 ONE SIDE INPUT
 0,5m									