

Kanlux

VARSO LED

PLAFONIERA LED ► CEILING-MOUNTED LED LIGHT FITTING



VARSO LED 18W-O; VARSO LED 18W-O-SE



VARSO LED 18W-L; VARSO LED 18W-L-SE



VARSO LED 24W-O; VARSO LED 24W-O-SE



Kanlux VARSO LED to rodzina plafonier hermetycznych ze zintegrowanym źródłem światła LED. Jest to znakomita propozycja zarówno dla inwestycji (spółdzielnie mieszkaniowe, hotele) jak i indywidualnych gospodarstw domowych gdzie potrzebna jest podwyższona odporność na wilgoć (IP54).

Atest PZH: Numer BK/K/0352/01/2018, ważny do 2023-05-30

Materiał obudowy: tworzywo sztuczne

Materiał klosza: tworzywo sztuczne

Kanlux VARSO LED is a family of hermetic ceiling light fixtures with an integrated LED light source. It is a great choice both for investment (housing co-operatives, hotels) and for individual households where increased resistance to humidity (IP54) is needed.

PZH attestation: Number BK/K/0352/01/2018, valid until 2023-05-30

VARSO LED + SE - version with a motion sensor

Enclosure material: plastic

Lampshade material: plastic



VARSO LED 18W-WW-O	26440	5905339264404	18	1620	3000	biały white
VARSO LED 18W-NW-O	26441	5905339264411	18	1700	4000	biały white
VARSO LED 18W-WW-L	26442	5905339264428	18	1620	3000	biały white
VARSO LED 18W-NW-L	26443	5905339264435	18	1700	4000	biały white
VARSO LED 24W-WW-O	26444	5905339264442	24	2160	3000	biały white
VARSO LED 24W-NW-O	26445	5905339264459	24	2280	4000	biały white
VARSO LED 24W-WW-L	26446	5905339264466	24	2160	3000	biały white
VARSO LED 24W-NW-L	26447	5905339264473	24	2280	4000	biały white
VARSO LED 18W-NW-L-SE	26980	5905339269805	18	1700	4000	biały white mikrofalowy microwave
VARSO LED 18W-NW-O-SE	26981	5905339269812	18	1700	4000	biały white mikrofalowy microwave
VARSO LED 24W-NW-L-SE	26983	5905339269836	24	2280	4000	biały white mikrofalowy microwave
VARSO LED 24W-NW-O-SE	26984	5905339269843	24	2280	4000	biały white mikrofalowy microwave

[V] 220-240 AC	[Hz] 50/60	120°	≥20000	20000 [h]	Ra ≥80	SMD	IP 54	House icon
Temperature icon -20+35	Mounting icon	Box icon	Beam angle icon 0,5-2,5	Beam diameter icon 0,5m	CE	ERL	Kanlux logo	Energy efficiency icon

