

# Kanlux FLM LED

NAŚWIETLACZ LED ▶ LED FLOODLIGHT



FLM LED 100W-NW



FLM LED 100W-NW



FLM LED 140W-NW



FLM LED 220W-NW



Model	Code	Power (W)	Beam Angle (°)	Luminous Flux (lm)	Beam Diameter (mm)	Beam Angle (°)	Color
FLM LED 100W-NW-60D	28520	5905339285201	100	12750	4000	60	czarny   black
FLM LED 100W-NW110/150	28521	5905339285218	100	12100	4000	X110/Y150	czarny   black
FLM LED 140W-NW-60D	28522	5905339285225	140	17850	4000	60	czarny   black
FLM LED 140W-NW110/150	28523	5905339285232	140	16950	4000	X110/Y150	czarny   black
FLM LED 220W-NW-60D	28524	5905339285249	220	28050	4000	60	czarny   black
FLM LED 220W-NW110/150	28525	5905339285256	220	26600	4000	X110/Y150	czarny   black



Naświetlacz Kanlux FLM MASTER to specjalna wersja naświetlacza FL MASTER, który wyposażony jest w dodatkowe typy soczewek: wąskostrumieniową - która zmienia kąt świecenia na 60° lub asymetryczną przy której kąt świecenia wynosi odpowiednio: X=110°, Y=150.

Produkty na indywidualne zamówienie po konsultacji z działem handlowym.

5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej

Materiał obudowy: stop aluminium

Materiał szyby ochronnej: szkło hartowane

Kanlux FLM MASTER floodlight is a special version of the FL MASTER floodlight, which is equipped with additional types of lenses - narrow-beam - which changes the angle of illumination to 60° - or asymmetrical - for which the beam angle is respectively: X=110°, Y=150.


Products available on individual order after consultation with the sales department

5 years Warranty under the terms of the warranty statement, available on our website


Enclosure material: aluminum alloy

Protective glass material: Tempered glass


[V] 220-240 AC	[Hz] 50/60	 ≥15000	 50000	 ≤ 60° MacAdam	 Ra ≥80	 SMD	 Eye safe	 Grounding	<b>IP</b> 65	 -40+40
 180	 IK 08	 0,4	 1	 1m	 CE	 EAC	 Kanlux			



FLM LED 100W



FLM LED 140W



FLM LED 220W