

Kanlux

REKA LED

OPRAWA ELEWACYJNA ► FACADE LUMINAIRE

NEW



REKA LED EL 7W-L-GR



REKA LED EL 7W-O-GR



REKA LED EL 7W-L-W



REKA LED EL 7W-O-W



Podstawową zaletą Kanlux REKA LED jest ciekawy wizualnie efekt świetlny, który lampa tworzy po włączeniu, a także dowolna regulacja strumienia światła za pomocą kłap maskujących. Kanlux REKA LED znajdzie zastosowanie przy oświetleniu elewacji budynków.

Regulacja kąta świecenia

Materiał obudowy: stop aluminium

The main advantage of the Kanlux REKA LED is an interesting visual effect, which the lamp creates when switched on, as well as the free luminous flux adjustment by means of masking flaps. The Kanlux REKA LED can be used for building-facade lighting.


Beam-angle adjustment

Enclosure material: aluminum alloy




Model	Code	Power [W]	Beam angle [°]	Light output [lm]	Temp. [K]	Mounting	Material	Beam direction
REKA LED EL 7W-L-GR	28990	5905339289902	7	max 360	4000	do nadbudowania na ścianie wall mounted	grafitowy graphite	góra i dół up and down
REKA LED EL 7W-O-GR	28991	5905339289919	7	max 380	4000	do nadbudowania na ścianie wall mounted	grafitowy graphite	góra i dół up and down
REKA LED EL 7W-L-W	28992	5905339289926	7	max 500	4000	do nadbudowania na ścianie wall mounted	biały white	góra i dół up and down
REKA LED EL 7W-O-W	28993	5905339289933	7	max 510	4000	do nadbudowania na ścianie wall mounted	biały white	góra i dół up and down

[V]	[Hz]	[°]	[h]	[lm]	Ra	COB	IP
220-240 AC	50/60	max 90	30000	≤ 6x Nachdam	≥ 80	COB	54
0,5m	-15+35			1		CE EAC	Kanlux



REKA LED EL-L



REKA LED EL-W