

# PRODUCT FAMILY DATASHEET

## OUTDOOR FACADE SPOT

Luminaires with rotatable head and directional light



---

### AREAS OF APPLICATION

- Outdoor
- Building facades
- Entrance lighting
- Gardens, balconies and other outdoor areas

---

### PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

---

### PRODUCT FEATURES




- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Adjustable modules: rotation angle 320°
- Diffuser made of opal polycarbonate
- Available in two housing colors: white and dark gray



TECHNICAL DATA

Product description	Electrical data	Photometrical data	Light technical data	Dimensions & weight				Colors & materials		Temperatures & operating conditions	Lifespan
	Nominal wattage	Luminous flux	Beam angle	Length	Width	Height	Product weight	Product color	Housing color	Ambient temperature range	Number of switching cycles
O FACADE SPOT 8 W 3000 K IP54 GY	8.00 W	440 lm	110 °	135.0 mm	90.0 mm	140.0 mm	600.00 g	Gray	Gray	-20...+40 °C	15000
O FACADE SPOT 8 W 3000 K IP54 WT	8.00 W	460 lm	110 °	135.0 mm	90.0 mm	140.0 mm	600.00 g	White	White	-20...+40 °C	15000

Product description	Lifespan L70/B50 at 25 °C	Capabilities	
		Dimmable	
O FACADE SPOT 8 W 3000 K IP54 GY	30000 h	No	
O FACADE SPOT 8 W 3000 K IP54 WT	30000 h	No	



O FACADE SPOT 8 W 3000 K IP54 GY, O FACADE SPOT 8 W 3000 K IP54 WT

O FACADE SPOT 8 W 3000 K IP54 GY

O FACADE SPOT 8 W 3000 K IP54 WT

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

---

#### APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

---

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075074729	Shipping carton box 6	385 mm x 170 mm x 355 mm	4072.00 g	23.23 dm <sup>3</sup>
4058075074743	Shipping carton box 6	385 mm x 170 mm x 355 mm	4072.00 g	23.23 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

#### REFERENCES / LINKS

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

---

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.