

CAT. N° 7 520 60



## ROTARY DIMMER WITHOUT NEUTRAL VALENA IN'MATIC - 240 V~ - 50 HZ

Pack (number of units)	1
Volume (dm <sup>3</sup> )	0,677
Weight (g)	145,00

### Product characteristics

#### Dimmers 240 V~ - 50 Hz

- Equipped with overvoltage and short-circuit protection
- When switched on, light up at the level set before last switch-off
- Can be remotely controlled via non-illuminated pushbuttons (Cat.No 7 520 11), with each push-button able to perform the ON/OFF and dimming function
- Screw terminals

#### Rotary dimmer without neutral

- For all types of lamps:
  - dimmable LEDs: 5 W to 75 W (10 lamps max.)
  - dimmable compact fluorescent lamps: 5 W to 75 W (10 lamps max.)
  - halogen with ferromagnetic or electronic transformer: 5 VA to 300 VA
  - fluorescent tube - ballast: 5 VA to 300 VA
  - halogen and incandescent 240 V~: 5W to 300W
- When switched on, gradually (2 seconds) lights up at the level set before last switch-off

### General characteristics

#### Valena™ IN'MATIC mechanisms - dimmers

- Valena In'Matic mechanisms are supplied with metal support, for claw or screw mounting
- To be equipped with Valena Life or Valena Allure cover plates and plates
- Supplied with mounted dust protection transparent shield
- Packaged in boxes

### Documentation

#### Catalogue pages & additional information

- [Description page \(p.496\)](#)
- [Selection chart \(p.509\)](#)
- [Selection chart \(p.513\)](#)

#### Installation & technical data

- [F01954EN-01](#)

#### Installation instructions & related documents

- [LE07432AB\\_hermes](#)