

CAT. N° 7 520 73



MOTION SENSOR WITH NEUTRAL VALENA IN'MATIC - SCREW/CLAW MOUNTING

Pack (number of units)	1
Volume (dm ³)	0,677
Weight (g)	117,00

Product characteristics

Motion sensors

- All sensors are compatible with any type of lamp
- Detection field 120°
- Detection range 8 m
- Integrated self-protection against overloads and short-circuits
- Screw terminals

Motion sensor with neutral

- Accepted power by lamp type:
 - LEDs: 0 to 50 W
 - Compact fluorescent: 0 to 50 W
 - LEDs, CFLs, Halogen with ferromagnetic or electronic ballast: 0 to 200 VA
 - fluorescent tubes with ferromagnetic or electronic ballast: 0 to 150 VA
- 230 V~ halogen, incandescent: 0 to 400 W
- Only one sensor per circuit
- No remote manual control with push-button
- Time delay setting from 10 s to 10 min
- Light level threshold setting from 5 lux to 1275 lux
- Standby consumption: 0.55 W

General characteristics

Valena™ IN'MATIC mechanisms - motion sensors, extractible emergency lamp, roller blind control, keycard switches

- Valena In'Matic mechanisms are supplied with metal support, for claw or screw mounting
- To be equipped with Valena Life or Valena Allure cover plates and plates
- Supplied with mounted dust protection transparent shield
- Packaged in boxes

Documentation



Catalogue pages & additional information

- [Description page \(p.497\)](#)
- [Selection chart \(p.509\)](#)
- [Selection chart \(p.513\)](#)



Installation & technical data

- F01966EN-03



Installation instructions & related documents

- [LE07972AD](#)