

CAT. N° 0 880 61



FLOOR BOX WITH REMOVABLE LID - IP66 - 4 MODULES - STAINLESS STEEL

Pack (number of units)	1
Volume (dm ³)	2,279
Weight (g)	921,00

Product characteristics

IP 66 floor boxes - 4 modules

- Supplied with lid and 4-module support frame for Mosaic Programme or Arteor mechanisms
- To be installed in flush-mounting backbox Cat.No 0 800 69 or directly in raised floor
- IK 09 with the lid closed
- Resistance to loads with lid closed: 10000 N

With removable lid - for indoor and outdoor use

- Can be equipped with cable exit accessory Cat.No 0 880 62
- IP 66 (when lid is closed)
- IP 54 (with cable exit accessory Cat.No 0 880 62 and plugs inserted into the sockets)
- Stainless steel finish

General characteristics

IP 66 floor boxes - 4 modules - for raised or concrete floors

- Conform to IEC/EN 60670-23

Documentation



Catalogue pages & additional information

- [Description page \(p.866\)](#)
- [Technical page \(p.866b\)](#)
- [Floor service outlet boxes and access units](#)



Installation & technical data

- [F02138EN-03](#)
- [F02138FR-03](#)



Installation instructions & related documents

- [LE07367AA-03](#)