



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Covered light facing down.
Characteristics of the luminaire	Modern design luminaire. For lighting private areas and public spaces.

## General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing$ 4mm, spacing 104mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter $\varnothing$ 7...10,5mm.
Type of light source	LED module AC integrated
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	1,41kg / 1,58kg
Box dimensions [cm]	23x16x8

## Technical data

LED module	Philips Fortimo DLM ES 1100/8xx G2 (Datasheet)
Light source wattage	9,5W
Luminaire wattage	9,5W
Lamp luminous flux	1080lm
Luminaire luminous flux	920lm
Light source efficiency	113,7lm/W
Efficiency of the luminaire	96,8lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,9
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	2,98A / 34,07 $\mu$ s
----------------	-----------------------

## Maximum number of luminaires of this type per MCB:

**B 10A:** 144, **B 16A:** 230, **C 10A:** 239, **C 16A:** 391

## Spare parts

ZS1330zx0009	Service set.
--------------	--------------

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

## Indexes

Index	Color	RAL
1330AL	ALUMINIUM	9006
1330GR	GRAPHITE	7016
1330W	WHITE	9003