



Type of luminaire

Type of luminaire	Bollard.
Photometric body	Uncovered light with rotationally symmetrical light distribution.
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas

General information

Materials	Wood - scandinavian impregnated pine and hot-dip galvanized steel. Wood - scandinavian impregnated pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120 °.
Terminal	Connection terminals: max 3x2.5mm ² , possibility to connect the luminaire in loops, max 3x1.5mm ² . Cable in a round wire with a maximum diameter of ø12.5mm
Type of light source	E27 lamp
Net / gross weight of luminaire	5,35kg / 6,35kg
Box dimensions [cm]	20x20x55

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimnable).

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Recommended light sources

Osram LED Parathom Classic E27 Philips Master LEDbulb / Ledbulb Classic E27

Spare parts

06281004	Lens.
08288002	Gasket.

Files to download

Photometric LDT files Photometric IES files
Manual

Indexes

Index	Color	RAL
1433B	BLACK	9005
1433GA	GALVANIZED	-