





举




Sande 1592XX0012 23.07.2021 v.12.3 www.norlys.com









Type of luminaire		
Type of lumianire	Reflector type luminaire.	
Photometric body	Symmetric light with 36° beam angle.	
Characteristics of the luminaire	Reflector type luminaire for permanent mounting. For lighting gardens and other private areas and public spaces. Possibility to adjust the direction of light in the vertical plane.	

General information			
Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. Nylon6 cable gland.			
Luminaire is equipped with spike (to stick into the ground surface) and foot (for permanent mounting).			
The luminaire is equipped with a cable type H05RN-F 3G1 with a length of 5m. For connection in a properly selected electrical installation box.			
LED Gu10 lamp, 36D			
Phase-dimming (TRIAC).			
1,25kg / 1,25kg			
26x16,5x12			

Technical data		
LED GU10 lamp	Philips MASTER LED ExpertColor 36D 5,5-50W PAR16 Gu10	
Light source wattage	5,5W	
Luminaire wattage	5,5W	
Lamp luminous flux	375lm	
Luminaire luminous flux	276lm	
Light source efficiency	68,2lm/W	
Efficiency of the luminaire	50,2lm/W	
Color temperature	3000K	
Colour consistency (McAdam ellipse)	SDCM3	
Colour rendering index CRI	90	
Rated life time L70/B50 at 25°C	40 000h	
Power Factor luminaire	PF 0,85	
Ta Rated temperature	+25°C	

This product contains light source of energy efficiency class A+

Accessories sold separately , xx - color of the luminaire	
1233XX0009	Cover.

Recommended light sources

Philips Master LED ExpertColor LED max Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10 5,5W<=>50W PAR16 Gu10

Philips Master LED max 4W PAR16 Gu10

Spare parts	
06000001	Lens.
08089000	Gasket.
46102508	LED Gu10 lamp.

Files to download

Photometric LDT files Photometric IES files Manual

Indexes		
Index	Color	RAL
1592B	BLACK	9005
1592GR	GRAPHITE	7016





