



Type of luminaire

Type of luminaire	Portable, in-ground mounting reflector luminaire.
Photometric body	Symmetric light with 40° beam angle.
Characteristics of the luminaire	Reflector type luminaire for permanent and portable mounting. For lighting private areas, parks, and other architectural concepts. Possibility to adjust the direction of light in the vertical plane

General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. Nylon6 cable gland.
Mounting method	The luminaire is equipped with a spike (for grounding) and anchor (for permanent mounting). Other accessories have to be ordered separately
Terminal	Luminaire equipped with 5m of H05RN-F 3G1 cable. To connect in a properly selected electrical installation box
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	1,19kg / 1,34kg
Box dimensions [cm]	25x15,5x10,5

Technical data

LED module	Cree XP-G3 DK1305003-VA05 (Datasheet)
Driver	VS ECXe 350.192 (186519)
Light source wattage	7W
Luminaire wattage	8,6W
Lamp luminous flux	854lm
Luminaire luminous flux	738lm
Light source efficiency	122lm/W
Efficiency of the luminaire	85,8lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>145 000h
LED photobiological threat	RG0 or RG1
Power Factor luminaire	PF 0,55
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Accessories sold separately, xx - color of the luminaire

1233XX0009	Cover
146ZX0009	Hermetic box IP68 8-track

Spare parts

06000001	Lens.
08089000	Gasket.
ZS1593zx0014	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1593B	BLACK	9005
1593GR	GRAPHITE	7016