



Type of luminaire	
Type of luminaire	Reflector type luminaire.
Photometric body	Symmetric light with 36° beam angle.
Characteristics of the luminaire	Reflector type luminaire for permanent mounting. For lighting gardens and other private areas and public spaces. Possibility to adjust the direction of light in the vertical and horizontal plane.

General information	
Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. Nylon6 cable gland.
Mounting method	Fixing of the luminaire: 2 oval holes 5x7mm, spacing 69x116mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED Gu10 lamp, 36D
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,3kg / 1,45kg
Box dimensions [cm]	29,5x17x16

Technical data	
LED GU10 lamp	Philips MASTER LED ExpertColor 36D 5,5-50W PAR16 Gu10
Light source wattage	5,5W
Luminaire wattage	5,5W
Lamp luminous flux	375lm
Light source efficiency	68,2lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	90
Rated life time L70/B50 at 25°C	40 000h
Power Factor luminaire	PF >0,85
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Accessories <small>sold separately</small>	
1233XX0009	Cover.
1234ZX0009	Spike.

Recommended light sources	
Osram LED Parathom Advanced / Pro max 4W PAR16 Gu10	Philips Master LED ExpertColor LED max 5,5W<=>50W PAR16 Gu10
Philips Master LED max 4W PAR16 Gu10	

Spare parts	
06000001	Lens.
08089000	Gasket.
46102508	LED Gu10 lamp.

Files to download	
Photometric LDT files	Photometric IES files
Manual	

Indexes		
Index	Color	RAL
1598B	BLACK	9005
1598GR	GRAPHITE	7016