



Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Modern design plafon type luminaire. For lighting private areas and public spaces.

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes \varnothing 5mm, spacing 164x242mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in max 3x1,5mm ² . A round wire in the isolation with a diameter \varnothing 7...10,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,8kg / 3,1kg
Box dimensions [cm]	35x27x9,5

Technical data

LED module	LUMENS LED DLM90C/230V/A 830
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1100lm
Luminaire luminous flux	387lm
Light source efficiency	110lm/W
Efficiency of the luminaire	38,7lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF >0,90
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+**

Inrush current	150mA/500 μ s
----------------	-------------------

Spare parts

06524002	Lens.
ZS1620zx0012	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1620AL	ALUMINIUM	9006
1620GR	GRAPHITE	7016