



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	A luminaire with a wide range of applications, for illuminating wall and facade surfaces as well as other architectural concepts

## General information

Materials	Front - hot-dip galvanized steel. Body - powder painted aluminum cast Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing the fixture: intermediate plate, 2 adjustment holes 5x10mm, 45mm spacing, directly 2 $\varnothing$ 5mm holes, 68mm spacing
Terminal	Connection terminals: max 3x2.5mm <sup>2</sup> , Possibility to connect the luminaire in loops, max 3x1.5mm <sup>2</sup> . Round insulated cable with a diameter of $\varnothing$ 7 ... 10.5mm
Type of light source	LED module, power supply
Light control	Trailing edge dimming

## Technical data

LED module	Philips Strip OC 0.5ft 550lm 8xx FC HV5 (Datasheet)
Driver	Philips Xitanium 7W 0,35A 20V TE SC 230V (Datasheet)
Light source wattage	4W
Luminaire wattage	5,3W
Lamp luminous flux	653lm
Luminaire luminous flux	347lm
Light source efficiency	163,3lm/W
Efficiency of the luminaire	65,5lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF > 0,9
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A++**

Inrush current	1A/15,2 $\mu$ s
----------------	-----------------

## Spare parts

ZS1715zx0011	LED module.
--------------	-------------

## Files to download

Photometric LDT files	Photometric IES files
BIM Revit	BIM ArchiCAD

## Indexes

Index	Color	RAL
1715GA	GALVANIZED	-