




Asker big 1717XX0010 23.07.2021 v.10.2 www.norlys.com



120 300

105°	105°
90°	90° -
-75°	75° .
60°	-20 -30
45°	45°
cd/k/m	60 η =
C0 - C180	0° 15° 30°



Type of luminaire	
Type of lumianire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

General information	
Materials	Front - hot-dip galvanized steel. Body - powder painted aluminum cast Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: mounting plate with 2 adjust holes 5x10mm, spacing 45mm, directly 2 holes ø5mm, spacing 68mm.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x1,5mm². A round wire in the isolation with a diameter of ø710,5mm.
Type of light source	E27 lamp
Box dimensions [cm]	31,5x14x16

Technical data	
E27 lamp	QA55 / LED A5560
Light source wattage	MAX 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class A+ D

Possibility to order luminaire with LED E27 lamp, type Philips Master LEDbulb 806lm/8,5W/2700K (dimmable).

Accessories sold separately	
46999021	LED E27 lamp.

Recommended light sources	
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Osram LED Parathom Classic / Retr	ofit E27	Philips Master LEDbulb / Classic / CorePro E27
Spare parts		
08120006	Gasket.	

Files to download	
Photometric LDT files	Photometric IES files
BIM Revit	BIM ArchiCAD

Indexes		
Index	Color	RAL
1717GA	GALVANIZED	-





