



STOCKHOLM Heavy duty galvanized steel or galvanized and powder coated bollard with opal or clear polycarbonate lens.


Art	Watt	Class	Type of light source:	Luminous flux	Colour temperature	Lifetime (L70/B50)	EEL	Lens	Height (cm)	Dimmable
299	-	II	E27	-	-	-	A+..D	Opal polycarbonate	28cm	-
1269	8,5W	II	LED E27	-	2700K	25 000h	A+	Opal polycarbonate	28cm	Dim. Triac
1268	10W	I	LED	294 lm	3000K	50 000h	A+	Opal polycarbonate	28cm	Dim. Triac
289	-	II	E27	-	-	-	A+..D	Opal polycarbonate	49cm	-
298	-	II	E27	-	-	-	A+..D	Clear polycarbonate	49cm	-
1469	8,5W	II	LED E27	294 lm	2700K	25 000h	A+	Opal polycarbonate	49cm	Dim. Triac
1260	10W	I	LED	294 lm	3000K	50 000h	A+	Opal polycarbonate	49cm	Dim. Triac

Accessories for Stockholm


205	Concreting anchor	p. 114
206	Anchoring support	p. 114

Art. 1269, i 1469: 8,5W LED E27 included, 806 lm, 2700K, 25000h, dimmable, EEL: A+

* **Stockholm with 4000K** available by request, contact your supplier.



Art. 299
Art. 1269
Art. 1268



Art. 289
Art. 298
Art. 1469
Art. 1260