

## STOCKHOLM



**STOCKHOLM** Heavy duty galvanized steel or galvanized and powder coated bollard with opal or clear polycarbonate lens.


| Art  | Watt | Class | Type of light source: | Luminous flux | Colour temperature | Lifetime (L70/B50) | EEL   | Lens                | Height (cm) | Dimmable   |
|------|------|-------|-----------------------|---------------|--------------------|--------------------|-------|---------------------|-------------|------------|
| 288  | -    | II    | E27                   | -             | -                  | -                  | A+..D | Opal polycarbonate  | 85cm        | -          |
| 297  | -    | II    | E27                   | -             | -                  | -                  | A+..D | Clear polycarbonate | 85cm        | -          |
| 1464 | 8,5W | II    | LED E27               | 294 lm        | 2700K              | 25 000h            | A+    | Opal polycarbonate  | 85cm        | Dim. Triac |
| 1265 | 10W  | I     | LED                   | 294 lm        | 3000K              | 50 000h            | A+    | Opal polycarbonate  | 85cm        | Dim. Triac |

### Accessories for Stockholm

|     |                   |        |
|-----|-------------------|--------|
| 205 | Concreting anchor | p. 114 |
| 206 | Anchoring support | p. 114 |

Art. 1464: 8,5W LED E27 included, 806 lm, 2700K, 25000h, dimmable, EEL: A+

\* **Stockholm with 4000K** available by request, contact your supplier.



Art. 288  
Art. 297  
Art. 1464  
Art. 1265