Завантажено з e27.com.ua

Stockholm 226XX0010 23.07.2021 v.10.1 www.norlys.com






STOCKHOLM 226

IР 54

E27

CE EAE 220-240V 50-60Hz



Type of luminaire			
Type of lumianire	Wall luminaire.		
Photometric body	Diffused, uncovered light.		
Characteristics of the luminaire	Plafon type, wall-mounted luminaire in Scandinavian design for general use. For lighting gardens, private areas and public spaces.		
General information			
Materials	Base - powder painted aluminum cast. Front - hot-dip galvanized steel or aluminum cast powder painted. Lens - clear polycarbonate, UV stabilized. Silicone gasket.		
Mounting method	Fixing of the luminaire: 2 holes ø5mm,spacing 80x80mm.		
Terminal	Connection terminals: max 2x2,5mm ² . Possibility to connect luminaire in loop max 2x1,5mm ² . A round wire in the isolation with a diameter of ø710,5mm.		
Type of light source	E27 lamp		
Technical data			
E27 lamp	QA55 / LED A5560		
Light source wattage	MAX 46W / LED 9W		
Ta Rated temperature	+25°C		
This product contains light source o	f energy efficiency	class A+ D	
Possibility to order the luminaire wit	h LED E27 Philips N	1aster LEDbulb 806lm /	8,5W / 2700K (dimmable).
Recommended light sour	ces		
Osram LED Parathom Classic E27		Philips Master LEDbulb / Ledbulb Classic E27	
Osram ECO PRO Classic 46<=>60W E27		Philips ECO Classic 42<=>60W E27	
Spare parts			
06220001	Lens.		
08550005	Gasket.		
Files to download			
Manual			
Indexes			
ITUCACO			
Index	Color		RAL

GALVANIZED

Norlys AS P.B 1014 Hoff, 0218 Oslo Hovfaret 4B, 0275 Oslo Norway +47 24 12 40 11 firmapost@norlys.no





226GA



-