



Stockholm 283XX0309 23.07.2021 v.09.1 www.norlys.com



Min.1740	Ø350
Max.2520 Min.1740	





Type of luminaire	
Type of lumianire	Accessories
Photometric body	Uncovered light.
Characteristics of the luminaire	Pole top luminaire in scandinavian design. For installation on a lighting pole with adjustable height 17402520mm. For lighting gardens, parks, and any other architectural concepts.

	other architectural concepts.
General information	
Materials	Hot-dip galvanized steel. Powder painted steel. Lens - transparent plastic PMMA.
Mounting method	Fixing of the luminaire: 3 holes Ø10,5 on a diameter Ø270mm every 120°. Set contains: art.2017- luminaire art. 3009/3011- lighting pole Other accessories need to be purchased separately.
Terminal	Connection terminals: max 4x2,5mm², possibility to connect luminaire in loop max 4x2,5mm². A round wire in the isolation on diameter ø712,5mm.
Type of light source	E27 lamp

Technical data	
E27 lamp	QA55 / LED A5560
Light source wattage	2x max 77W / LED 9W
This product contains light source of energy efficiency class A+ D	

Accessories sold separately	
405ZX0009	Concreting anchor.
406ZX0009	Ground anchor.

Recommended light sources	
Philips Master LEDbulb / Classic / CorePro E27	Osram ECO PRO Classic 77<=>100W E27
Philips ECO Classic 70<=>100W E27	Philips Master LEDbulb / LEDbulb Classic E27

Spare parts	
06281002	Lens.
08281001	Gasket.

Files to download	
Photometric LDT files	Photometric IES files

Indexes		
Index	Color	RAL
283B	BLACK	9005
283GA	GALVANIZED	-





