



## Type of luminaire

Type of luminaire	Bollard.
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

## General information

Materials	Hot-dip galvanized steel. Lens - transparent plastic PMMA. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø56mm every 120°.
Terminal	Connection terminals: max 3x4mm <sup>2</sup> , possibility to connect luminaire in loop max 3x2,5mm <sup>2</sup> . A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	9,56kg / 10,49kg
Box dimensions [cm]	21x21,5x92

## Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

## Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

## Spare parts

06281005	Lens.
08288002	Gasket.

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
297B	BLACK	9005
297GA	GALVANIZED	-