


Stockholm 299XX0010 23.07.2021 v.10.2 www.norlys.com



Type of luminaire	
Type of lumianire	Bollard.
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the lumina	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.
General information	
Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø56mm every 120 °.
Terminal	Connection terminals: max 3x2,5mm². A round wire in the isolation with a diameter of max ø12mm.
Type of light source	F27 Jamp

	and public spaces.		
General information			
Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.		
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø56mm every 120 °.		
Terminal	Connection terminals: max 3x2,5mm². A round wire in the isolation with a diameter of max ø12mm.		
Type of light source	E27 lamp		
Net / gross weight of luminaire	4,45kg / 4,85kg		
Box dimensions [cm]	32x20x20		



Technical data	
E27 lamp	QA55 / LED A5560
Light source wattage	max 46W / LED 9W
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class A+ D

Accessories sold separately		
205ZX0010	Concreting anchor.	
206GA0010	Ground anchor.	
206GA0S10	Anchoring support.	

135°	150°	165°	180°	165°	150°	135
		1	60	+	\times	\searrow
	\times $/$	7-+	50	+	$\langle \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$	
120°	\times	1	40	47	\times	120
/ /	\angle \nearrow		30		\wedge	\prec
	1/1/	\times	20	$/\times$	7-1	105
	1	imes imes	M	\times	1	+1
90°			\sim		1	90
	/ L	++		\Box		
75°	17	+	$Z/T\mathbb{N}$	XX	11	1 / /5
13/		\checkmark	///	\mathcal{X}		/ /1
	$\langle \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$	\wedge		$\Gamma \times \Gamma$	\times $^{\prime}$	\times
60°	(X)	\times 7		TX	$^{\prime}$ \times ,	60
	\times	47	+	1	$\langle \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$	V
cd/klm C0 - C	180	C90 - C270	_	-+	\times	/1=/
45°	30°	15°	0°	15°	30°	45

Recommended light sources		
Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27	
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27	

Spare parts	
06281004	Lens.
08288004	Gasket.

Files to download	
Photometric LDT files	Photometric IES files

Indexes		
Index	Color	RAL
299B	BLACK	9005
299GA	GALVANIZED	-

299 H=0.28m			2m
		1	
	2.5		lx
	5		
	10		
0m			0m 2m



