



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Double-sided light facing up and down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

## General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: aluminum plate with 2 holes 5x10mm spacing 45mm, or directly: 2 holes ø5mm spacing 68mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of ø7...10,5mm.
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net weight of luminaire	2,27kg
Box dimensions [cm]	31,5x14x16

## Technical data

2 LED modules	Philips LED Strip 0.5ft 550lm 840 FC LV4
Driver	Xitanium 8W 0.2A 40V TE SC 230V 12NC: 929001421006 EOC: 929001421006
Light source wattage	6,8W
Luminaire wattage	8,5W
Lamp luminous flux	1154lm
Light source efficiency	169,7lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF >0,90
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A++**

Inrush current	1,65A/16,5µs
----------------	--------------

## Maximum number of luminaires of this type per MCB:

**B 10A:** 160, **B 16A:** 254, **C 10A:** 264, **C 16A:** 431

## Spare parts

08120006	Gasket.
46999610	Power supply.
46999615	LED module.

## Files to download

Manual

## Indexes

Index	Color	RAL
5019AL	ALUMINIUM	9006
5019B	BLACK	9005
5019GR	GRAPHITE	7016
5019W	WHITE	9003