



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Single-sided light with 62° beam angle facing down.
Characteristics of the luminaire	A luminaire with a wide range of applications, among others for lighting: wall and facade surfaces and other architectural concepts

## General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket. EPDM cable gland.
Mounting method	Mounting of the luminaire: 2 holes ø7mm, spacing 100x80mm
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , Possibility to connect the luminaire in loops, max 3x1,5mm <sup>2</sup> , Round insulated cable with a diameter of ø7 ... 10,5mm
Type of light source	LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	5,1kg / 5,1kg
Box dimensions [cm]	22,5x19,5x32

## Technical data

2 LED modules	Cree JK3030 no.1805004 (Datasheet)
Driver	Philips Xitanium 10W 0,5A 20V TE SC 230V (Datasheet)
Light source wattage	9W
Luminaire wattage	11,8W
Lamp luminous flux	1284lm
Light source efficiency	142,7lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF 0,9
THD factor	20%
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A++**

Inrush current	3,36A / 36µs
----------------	--------------

## Spare parts

ZS5034zx0G09	Service set.
--------------	--------------

## Files to download

Manual	BIM Revit
BIM ArchiCAD	

## Indexes

Index	Color	RAL
5034AL	ALUMINIUM	9006
5034GR	GRAPHITE	7016