



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Single-sided light facing down.
Characteristics of the luminaire	Luminaire with a wide range of applications for example for illumination of walls and facade surfaces or any other architectural concepts.

## General information

Materials	Powder painted aluminum cast. Lens - transparent polycarbonate with structure, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: mounting plate with 2 adjust holes 7x10mm, spacing 100mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of $\varnothing$ 7...10,5mm.
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	2kg / 2kg
Box dimensions [cm]	34x17x16,5

## Technical data

LED module	Philips LED SLM C 830 1203 L09 1619 G7
Light source wattage	6,7W
Luminaire wattage	8,5W
Lamp luminous flux	1059lm
Luminaire luminous flux	682lm
Light source efficiency	158,1lm/W
Efficiency of the luminaire	80,2lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
Power Factor luminaire	PF 0,90
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A++**

Inrush current	1,65A / 16,5 $\mu$ s
----------------	----------------------

## Maximum number of luminaires of this type per MCB:

**B 10A:** 160, **B 16A:** 254, **C 10A:** 264, **C 16A:** 431

## Spare parts

06120004	Lens.
46999610	Power supply.
46999691	LED module.
ZS517ZX0013	Service set.

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
517AL	ALUMINIUM	9006
517GR	GRAPHITE	7016
517W	WHITE	9003