



Type of luminaire

Photometric body	Symmetric light directed down.
Characteristics of the luminaire	Pole luminaire, mounted ø120mm.

General information

Materials	Powder painted aluminum cast. Lens - transparent plastic PMMA. Silicone gasket. Nylon6 cable gland.
Mounting method	Luminaire mounting: 3 ø9mm holes with ø65mm diameter every 120 °
Terminal	Hermetic box IP68: Connection terminals: max 4x4mm ² , Possibility of connecting the luminaire in a max 4x2,5mm ² loop. Cable in a round tire with a diameter of ø8 ... 12mm or ø10 ... 14mm The luminaire is equipped with an revision door.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	13kg / 14,01kg
Box dimensions [cm]	15x15x260
Side area of luminaire	0,33m ²

Technical data

Luminaire wattage	10W
Luminaire luminous flux	959lm
Light source efficiency	110lm/W
Efficiency of the luminaire	95,9lm/W
ULOR	2%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Energy Efficiency Index	A+
Power Factor luminaire	PF >0,97
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	-30...+25°C
Inrush current	150mA / 500µs

Accessories sold separately

6130zx0009	Concreting anchor
------------	-------------------

Spare parts

46999402	LED module.
----------	-------------

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
6105AL	ALUMINIUM	9006
6105GR	GRAPHITE	7016