



## Type of luminaire

Type of luminaire	Bollard.
Photometric body	Four side light distribution covered from the top.
Characteristics of the luminaire	Bollard luminaire and electricity distributor 220 ... 240V. For lightning private areas and public spaces such as: gardens, camping's, etc.

## General information

Materials	Hot-dip galvanized steel. Powder painted steel. Lens - clear polycarbonate, UV stabilized. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 85\text{mm}$ every $120^\circ$ .
Terminal	Connection terminals: max $5 \times 4\text{mm}^2$ , possibility to connect luminaire in loop max $5 \times 4\text{mm}^2$ . A round wire in the isolation on a diameter of max $\varnothing 20\text{mm}$ .
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	11,94kg / 12,44kg
Box dimensions [cm]	15x15x91

## Technical data

4 LED modules.	Cree JK3030 3000K no.1805004
Driver	Osram OT FIT 15/220-240/500 LT2 S
Light source wattage	9,9W
Luminaire wattage	12,7W
Lamp luminous flux	1424lm
Luminaire luminous flux	593lm
Light source efficiency	143,8lm/W
Efficiency of the luminaire	46,7lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF > 0,85
Ta Rated temperature	+25°C

This product contains light sources of energy efficiency class **A++**

Inrush current	24A / 174 $\mu\text{s}$
----------------	-------------------------

## Maximum number of luminaires of this type per MCB:

**B 10A: 17, B 16A: 28, C 10A: 29, C 16A: 47**

## Accessories sold separately

207GA0010	Ground/concrete base.
208ZX0009	Concrete base.

## Spare parts

06890003	Lens.
08890000	Gasket.
46999735	Power supply.

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
893B	BLACK	9005
893GA	GALVANIZED	-