



Type of luminaire	
Type of luminaire	Bollard with energy distributor.
Photometric body	Four side light distribution covered from the top.
Characteristics of the luminaire	Bollard luminaire and electricity distributor 220 ... 240V. For lightning private areas and public spaces such as: gardens, campings, sailing harbors, etc. The luminaire is sold without mounting elements for ground / concrete.

General information	
Materials	Hot-dip galvanized steel. Powder painted steel. Lens - clear polycarbonate, UV stabilized.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø85mm every 120°. Concreting anchor included to the luminaire.
Terminal	Connection terminals: max 5x4mm ² , possibility to connect luminaire in loop max 5x4mm ² . A round wire in the isolation on a diameter of max ø20mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	11,8kg / 12,3kg
Box dimensions [cm]	15x15x91

Technical data	
E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
ULOR	0%
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **A+ D**

Possibility to order the luminaire with LED E27 Philips Master LEDbulb 806lm / 8,5W / 2700K (dimnable).

Accessories <small>sold separately</small>	
208ZX0009	Concreting anchor.
46999021	LED E27 lamp.

Recommended light sources	
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27
Osram LED Parathom Classic / Retrofit E27	Philips Master LEDbulb / Classic / CorePro E27

Files to download
Manual

Indexes		
Index	Color	RAL
899B	BLACK	9005
899GA	GALVANIZED	-