


SOFT LED 60×6

aluminium, PC / aluminium, PC / алюминия, PC

9541 ○ WH 9537 ● GR

⊖ 1×T8 LED, 11W, included



SOFT LED 60×20

aluminium, PC / aluminium, PC / алюминия, PC

9534 ○ WH 9532 ● GR

⊖ 2×T8 LED, 11W, included



SOFT LED 60×6 9527 WH




SOFT LED 60×6

aluminium, PC / aluminium, PC / алюминия, PC

9527 ○ WH 9525 ● GR

⊖ 1×T8 LED, 11W, included




SOFT LED 90×6

aluminium, PC / aluminium, PC / алюминия, PC

9540 ○ WH 9536 ● GR

⊖ 1×T8 LED, 16W, included



SOFT LED 90×20

aluminium, PC / aluminium, PC / алюминия, PC

9533 ○ WH 9531 ● GR

⊖ 2×T8 LED, 16W, included



SOFT LED 90×6 9524 GR




SOFT LED 90×6

aluminium, PC / aluminium, PC / алюминия, PC

9526 ○ WH 9524 ● GR

⊖ 1×T8 LED, 16W, included




SOFT LED 120×6

aluminium, PC / aluminium, PC / алюминия, PC

9538 ○ WH 9535 ● GR

⊖ 1×T8 LED, 22W, included



SOFT LED 60×60

aluminium, PC / aluminium, PC / алюминия, PC

9530 ○ WH 9528 ● GR

⊖ 5×T8 LED, 11W, included



SOFT LED 60×20 9523 WH



SOFT LED 60×20

aluminium, PC / aluminium, PC / алюминия, PC

9523 ○ WH 9522 ● GR

⊖ 2×T8 LED, 11W, included

NAME	SIZE	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >)	INPUT	POWER FACTOR	LIFETIME	MATERIAL
LED TUBE T8	60 cm	11W	3000K	950-1000 lm	200°	80	~230V, 50Hz	> 0,9	25 000 h	CLEAR GLASS
LED TUBE T8	90 cm	16W	3000K	1400-1500 lm	200°	80	~230V, 50Hz	> 0,9	25 000 h	CLEAR GLASS
LED TUBE T8	120 cm	22W	3000K	2000-2100 lm	200°	80	~230V, 50Hz	> 0,9	25 000 h	CLEAR GLASS