



HELIOS 8992 WH




EOL 8988 WH



CEILING COB 6971 WH



CEILING COB 6972 WH




HELIOS

plastik, PC dyfuzor / plastic, PC diffuser / пластик, РС диффузор

8991 ○ WH - 3000K

8992 ○ WH - 4000K

🔧 cut out ø 85 mm




EOL

plastik, PC dyfuzor / plastic, PC diffuser / пластик, РС диффузор

8988 ○ WH - 3000K

8990 ○ WH - 4000K

🔧 cut out ø 85 mm




CEILING COB

plastik / plastics/ пластик

6971 ○ WH

🔧 cut out ø 70 mm



CEILING COB

plastik / plastics/ пластик

6972 ○ WH

🔧 cut out ø 90 mm

Item No.	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >=)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION	LIFETIME
8988	5W LED	3000K	265 lm	30°	80	~200-240V, 50Hz	☐	0,5	IP 44	20 000 h
8990	5W LED	4000K	265 lm	30°	80	~200-240V, 50Hz	☐	0,5	IP 44	20 000 h
8991	5W LED	3000K	260 lm	80°	80	~200-240V, 50Hz	☐	0,5	IP 44	20 000 h
8992	5W LED	4000K	260 lm	80°	80	~200-240V, 50Hz	☐	0,5	IP 44	20 000 h

Item No.	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >=)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION	LIFETIME
6971	5W	3000K	380 lm	60°	81	~230V, 50Hz	☐	0,55	IP 20	20 000 h
6972	10W	3000K	780 lm	60°	81	~230V, 50Hz	☐	0,55	IP 20	20 000 h