




ASSOS 9124 BL



ASSOS


aluminium, szkło / aluminium, glass / алюминий, стекло

9124 ● BL

2×GU10, max 10W
IP 54



ASSOS 9123 BL



ASSOS


aluminium, szkło / aluminium, glass / алюминий, стекло

9123 ● BL

1×GU10, max 10W
IP 54



BRICK 3408 GR



BRICK


aluminium, szkło / aluminium, glass / алюминий, стекло

3408 ● GR

1×E27, max 60W
IP 65



DISC LED 6910 BL




DISC LED

aluminium, PC / aluminium, PC / алюминий, PC

6910 ● BL



UNIT LED 9122 BL



UNIT LED

aluminium / aluminium / алюминий

9122 ● BL

Item No.	POWER	COLOUR TEMP.	LUMINOUS FLUX	BEAM ANGLE	COLOUR RENDERING INDEX (CRI >=)	INPUT	SAFETY TYPE	POWER FACTOR	INGRESS PROTECTION	LIFETIME
6910	4×1W LED	3000K	350 lm	67°	80	~220-240V, 50Hz	⊕	0,46	IP 44	10 000 h
9122	2×5W LED	3000K	727 lm	110°	80	~220-240V, 50Hz	⊕	0,89	IP 54	20 000 h