


**BULB LED G9, 7W**

ceramic housing, plastic PC

☐ 9197 3000K ☐ 10933 4000K

**BULB LED G9, 7W 9197**




**REFLECTOR LED, GU10, R35, 4W**

plastic

☐ 10230 3000K ☐ 10231 4000K

**REFLECTOR LED, GU10, R35, 4W 10230**




**BULB LED G9, 4W**

plastic PC

☐ 7503 3000K ☐ 7504 4000K

**BULB LED G9, 4W 7504**




**REFLECTOR LED, GU10, R50, 7W**

plastic

☐ 9180 3000K ☐ 9178 4000K  
 ■ 8348 3000K ■ 8347 4000K

**REFLECTOR LED, GU10, R50, 7W 8347**



**BULB LENS LED, G9, 3W**

ceramic housing, plastic PC

☐ 9173 3000K ☐ 8447 4000K

**BULB LENS LED, G9, 3W 9173**

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
9197	7W LED	3000K	750 lm	360°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
10933	7W LED	4000K	900 lm	360°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
7503	4W LED	3000K	380 lm	360°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
7504	4W LED	4000K	390 lm	360°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
9173	3W LED	3000K	330 lm	90°	≥ 80	~220-230 V, 50/60 Hz	>0.5	25000h
8447	3W LED	4000K	310 lm	90°	>80	~220-230 V, 50/60 Hz	>0.5	25000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime
9180	7W LED	3000K	600 lm	50°	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
9178	7W LED	4000K	600 lm	50°	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
8348	7W LED	3000K	600 lm	50°	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
8347	7W LED	4000K	600 lm	50°	≥ 80	~220-230 V, 50/60 Hz	>0.7	25000h
10230	4W LED	3000K	370 lm	70°	>80	~220-230 V, 50/60 Hz	>0.5	20000h
10231	4W LED	4000K	400 lm	70°	>80	~220-230 V, 50/60 Hz	>0.5	20000h

☐ WHITE

☐ WHITE ■ BLACK