
LUMINAIRE PHOTOMETRIC TEST REPORT

8775 CL KOS LED 24W, 3000K



Description Lines

Manufacturer:	NOWODVORSKI LIGHTING
Model name:	8775 CL KOS LED 24W,3000K
File name:	8775 CL KOS LED 24W,3000K.ltd
Date:	2019-08-19
Report number:	EF 19/08/2019/14
Diameter:	225mm
Height:	36mm
IP rating:	IP 44
Protection class:	II
Dimmable:	No

Equipment

Test system:	EVERFINE GO-2000B_V1 SYSTEM V2.00.417
Temperature:	25 +/-1 °C
Humidity:	65.0%
γ interval:	1 deg
C interval:	10 deg
γ range:	0-90 deg
Measurement distance:	6.56 m

Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208


Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12

www.nowodvorski.com

Photometric data

Total luminous flux:	2183.83 lm
Color temperature:	3067 K
x:	0.4293
y:	0.3961
Color rendering index:	84.7
Wattage:	22.196 W
U	230.61 V
I	0.1910 A
Power factor:	0,5039
Luminous efficacy:	98.39 lm/W
Flux in lower hemisphere:	100.0%
Flux in upper hemisphere:	0.0%
Maximum luminous intensity:	838.8 cd
Light output ratio (LOR):	100.00%

Beam cone diagram
Beam angle 100°




Nowodvorski sp. j.

ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208

Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12


www.nowodvorski.com

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Luminous intensity [cd]
 C0-C180 ————
 C90-C270 ————

Spectral distribution



Nowodvorski sp. j.
 ul. Bojemskiego 11, 42-202 Częstochowa, POLSKA, NIP: PL 5731015208
 Tel. +48 34 344 91 10, 344 91 11, fax +48 34 344 91 12
www.nowodvorski.com