




PROFILE MIKE 7661



PROFILE MIKE

Painted aluminum, plastic

7662 7661


1xGU10, max 15W



PROFILE ZOOM LED 7625



PROFILE INDIA 7657




PROFILE INDIA

Painted aluminum, plastic

7656 7657

1xGU10, max 15W



PROFILE ZOOM LED

Painted aluminum, plastic

7623 3000K 7625 3000K

7624 4000K 7626 4000K

BEAM CONE


BEAM ANGLE 15°



BEAM ANGLE 50°



PROFILE FOKUS 7621



PROFILE FOCUS LED

Painted aluminum, plastic

7618 3000K 7621 3000K

7620 4000K 7622 4000K

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection
7618	9W LED	3000K	440 lm	36°	>90	220-230 V, 50/60 Hz	□	>0.9	IP20
7620	9W LED	4000K	480 lm	36°	>90	220-230 V, 50/60 Hz	□	>0.9	IP20
7621	9W LED	3000K	430 lm	36°	>0.9	220-230 V, 50/60 Hz	□	>0.9	IP20
7622	9W LED	4000K	460 lm	36°	>90	220-230 V, 50/60 Hz	□	>0.9	IP20
7623	9W LED	3000K	550 lm	15-50°	>90	220-230 V, 50/60 Hz	□	>0.9	IP20
7624	9W LED	4000K	580 lm	15-50°	>90	220-230 V, 50/60 Hz	□	>0.9	IP20
7625	9W LED	3000K	490 lm	15-50°	>90	220-230 V, 50/60 Hz	□	>0.9	IP20
7626	9W LED	4000K	520 lm	15-50°	>90	220-230 V, 50/60 Hz	□	>0.9	IP20