

## 13 Wall &amp; Ceiling LED&gt;The SMD Cylinders Aluminium

12125L/W/W



25W COB LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



## Downloads





## Dimensions




## Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12125L/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	115mm
Diameter	162mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No


Gear		Built In	
Fitting + Driver			
Input Voltage		220-240V	
50 Hz		Yes	
60 Hz		Yes	
Safety Class			
Power(Watts)		25W	
IP Rating		IP40	
Light Source		LED built in	
Dimmable		No	
F Mark			

Fitting			
Input Type		Constant Current	
Input Current		600mA	
Voltage		40V	
Power(Watts)		24W	
IP Rating		IP20	
Light Source		LED built in	
LED Type		SMD 5630	
LED Brand		Samsung	
LED Number		48	

Gear			
Gear Type		Led Driver	
Input Voltage		220-240V	
50 Hz		Yes	
60 Hz		Yes	
Power(Watts)		16,2-25,2W	

Power Factor	0,9
Constant Current	Yes
600mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic

#### Illumination Data

Colour Temperature	3000K
Lumen Output	2050lm
Light Efficiency	82lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

#### Packing Info

Box Length	17,5cm
Box Width	17,5cm
Box Height	12,5cm
Box Weight	0.827kg
Pcs/Carton	36
Barcode	5291889041009
HS Code	9405409900

Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to  
**one light!**

one  
LIGHT

