


INSTALLATION MANUAL

61092

LED
BUILT IN


2,5W | IP65 | SMD LED | CCT Adjustable | Dimmable | Die cast

 Rechargeable USB socket.
2x4400mAh lithium battery.

80
CRI

one
LIGHT

A CHARGE
Order separately USB adaptor 61000A or charging station 61000

USB adaptor (DC5V 1A)

100% → 0%
10 hours
(100% light intensity)

MAX 6.5 HOURS
(full recharging)

B TOUCH SWITCH & MEMORY of BRIGHTNESS

Each time the table lamp is switched ON, the lighting brightness remains the same as in previous setting.

TOUCH STEPLESS DIMMER
⚠ Only works when the light is ON

C CCT ADJUSTABLE
⚠ Only works when the light is OFF

Hold Time > 4s
OFF

CCT MODE
BLUE LIGHT ON

2700K
3000K
Touch Time < 0,5s

Hold Time > 4s
OFF

*The charging base is IP20

Warnings:

1. Do not cover the fitting.
2. The batteries should not be opened, destroyed or incinerate.
3. Do not short circuit terminals, or over charge the battery, forced-over-discharge, throw to fire.
4. Do not crush or puncture the battery, or immerse in liquids.
5. Avoid direct sunlight.
6. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change.
7. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

www.1-light.eu