

06 Downlights Fixed LED>Panels For Germany/Austria

50148AU/W/W



UGR19 62x62 recessed LED panel for T-rail false ceilings. Can be recessed or suspended. Uniform lighting, ideal for commercial applications.

Requires 1200mA LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Must be ordered separately




89048

Accessories



050017



050108



89048T



89050L



89050TLD

Physical Specification

Item Group	06 Downlights Fixed LED
Family	Panels For Germany/Austria
Order Code	50148AU/W/W
Colour	White
Material	Aluminium
Diffuser Material	Acrylic
Shape	Rectangular
Length	620mm
Width	620mm
Height	20mm
Recessed T-Ceiling	Yes
Depth Required	55mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Fitting	
Input Type	Constant Current
Input Current	1200mA
Safety Class	III
Power(Watts)	48W
IP Rating	IP20
Light Source	LED built in

LED Type

SMD 2835

Завантажено з e27.com.ua

LED Brand

Epistar

LED Number

240

Illumination Data

Colour Temperature

3000K

Lumen Output

4000lm

Light Efficiency

83,33lm/W

CRI

80

Beam Angle

120°

Illumination Diagram



UGR

19

Packing Info

Box Length

72cm

Box Width

65cm

Box Height

4,5cm

Box Weight

3,4Kg

Pcs/Carton

4

Barcode

5291889044628

HS Code

9405109890

Certification & Warranty

Warranty

2 Years

[Завантажено з e27.com.ua](http://e27.com.ua)

Average Lifetime

30000 hours

Weee Directive

Yes

switch to
one light!

one
LIGHT

